

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 September 2004 (30.09.2004)

PCT

(10) International Publication Number
WO 2004/082409 A1

- (51) International Patent Classification⁷: **A24C 5/34**, G01N 21/93, G01B 11/10, G01N 21/952
- (21) International Application Number: PCT/GB2004/001177
- (22) International Filing Date: 19 March 2004 (19.03.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0306467.2 20 March 2003 (20.03.2003) GB
- (71) Applicant (for all designated States except US): **MOLINS PLC** [GB/GB]; 11 Tanners Drive, Blakelands, Milton Keynes MK14 5LU (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **WILSON, Ronald, Frederick** [GB/GB]; 16 Edmonds Close, Page Hill, Buckingham, Buckinghamshire MK18 1YR (GB). **PITT, Garry, John** [GB/GB]; 10 Osterley Close, Newport Pagnell, Buckinghamshire MK16 0EZ (GB). **IRONS, Timothy, G.** [GB/GB]; 41 Naylor Avenue, Kempston, Bedford MK42 7SQ (GB). **EVERITT, William, A., H.** [GB/GB]; 88 Sovereigns Quay, Commercial Road, Bedford MK40 1TF (GB).
- (74) Agents: **CRUMP, Julian, Richard, John et al.**; FJ Cleveland, 40-43 Chancery Lane, London WC2A 1JQ (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
- with international search report
 - before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMPROVEMENTS IN OR RELATING TO MACHINE VISION EQUIPMET

(57) Abstract: A method of setting-up machine vision equipment is disclosed, which equipment comprises imaging means comprising a camera defining a field of view and being adapted to form an image of a test object within said field of view, and processing means for processing said image for determining one or more physical properties of said test object, and first supporting means for supporting a test object at a predetermined distance from said camera within said field of view; said method being characterised by: providing second supporting means for supporting at least one reference object; placing a reference object having at least one accurately known dimension on said second supporting means; selectively moving one or more of said camera, said first supporting means and said second supporting means, such that said reference object is brought into the camera's field of view at said predetermined distance from said camera; imaging said reference object to obtain at least one image, and processing said at least one image to determine the optimum configuration of the imaging means; and thereafter adjusting the configuration of said imaging means to said optimum configuration. Also disclosed is a dimensionally stable reference object having at least one accurately known dimension which is fabricated from a ceramic material having a low reflectance or albedo value. Preferably, the reference object comprises a cylindrical bar having an accurately known diameter. Said ceramic material may comprise a ceramic alumina.